

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims in accordance with the following:

1. (ORIGINAL) A method of driving a plasma display device applying a first voltage between sustain discharge electrodes so as to perform discharge in a display cell, comprising:
a removal step of removing wall charges formed, by sustain discharge performed between said sustain discharge electrodes, on an address electrode for selecting said display cell.

2. (ORIGINAL) The method according to claim 1, wherein
said removal step comprises a wall charge formation step of applying a second voltage to at least one of said sustain discharge electrodes and a self-erase step of applying a third voltage to said address electrode, and
said second voltage is a voltage for forming, on said address electrode by sustain discharge performed between said sustain discharge electrodes, wall charges capable of self-erase discharge performed between said address electrode and at least one of said sustain discharge electrodes in said self-erase step.

3. (CURRENTLY AMENDED) The method according to claim 2, wherein in said wall charge formation step, said second voltage is applied to one of said sustain discharge electrodes, and the other electrode is set at ground level.

4. (CURRENTLY AMENDED) The method according to claim 2, wherein in said wall charge formation step, said second voltage is applied to one of said sustain discharge electrodes, and then said second voltage is applied to the other electrode.

5. (ORIGINAL) The method according to claim 1, wherein said removal step is arranged between subfields each comprising a reset step, a address step, a sustain discharge

step.

6. (ORIGINAL) A method of driving a plasma display device applying a first voltage between sustain discharge electrodes so as to perform discharge in a display cell, wherein after sustain discharge is performed between said sustain discharge electrodes, a second voltage that is a voltage twice a power supply voltage for generating a pulse for sustain discharge is applied to at least one of said sustain discharge electrodes, and during or after applying said second voltage, a third voltage is applied to an address electrode for selecting said display cell.

7. (ORIGINAL) The method according to claim 6, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse simultaneously and driven by scanning pulse separately, and said second voltage is applied to the X-electrode.

8. (ORIGINAL) The method according to claim 6, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse simultaneously and driven by scanning pulse separately, and said second voltage is applied to the Y-electrode.

9. (ORIGINAL) The method according to claim 6, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse simultaneously and driven by scanning pulse separately, and said second voltage is applied to the Y-electrode, and then, said second voltage is applied to the X-electrode.

10. (ORIGINAL) The method according to claim 6, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse simultaneously and driven by scanning pulse separately, and

said second voltage is applied to the X-electrode, and then, said second voltage is applied to the Y-electrode.

11. (ORIGINAL) A method of driving a plasma display device applying a first voltage between sustain discharge electrodes so as to perform discharge in a display cell, wherein a second voltage that is a voltage twice a power supply voltage for generating a pulse for sustain discharge is applied to at least one of said sustain discharge electrodes as a final pulse for sustain discharge performed between said sustain discharge electrodes, and during or after applying said second voltage, a third voltage is applied to an address electrode for selecting said display cell.

12. (ORIGINAL) The method according to claim 11, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse simultaneously and driven by scanning pulse separately, and said second voltage is applied to the X-electrode.

13. (ORIGINAL) The method according to claim 11, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse simultaneously and driven by scanning pulse separately, and said second voltage is applied to the Y-electrode.

14. (ORIGINAL) The method according to claim 11, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse simultaneously and driven by scanning pulse separately, and said second voltage is applied to the Y-electrode, and then, said second voltage is applied to the X-electrode.

15. (ORIGINAL) The method according to claim 11, wherein said sustain discharge electrodes comprise X-electrodes which are driven by sustain discharge pulse simultaneously, and Y-electrodes which are driven by sustain discharge pulse

simultaneously and driven by scanning pulse separately, and

said second voltage is applied to the X-electrode, and then, said second voltage is applied to the Y-electrode.

16. (AS ONCE AMENDED) A plasma display device applying a first voltage between sustain discharge electrodes so as to perform discharge in a display cell, comprising:

a control circuit applying a second voltage to at least one of said sustain discharge electrodes and applying a third voltage to an address electrode for selecting said display cell, wherein said second voltage is a voltage which forms, on said address electrode by sustain discharge performed between the sustain discharge electrodes, wall charges capable of self-erase discharge between said address electrode and at least one of said sustain discharge electrodes by said third voltage.

17. (AS ONCE AMENDED) A plasma display device applying a first voltage between sustain discharge electrodes so as to perform discharge in a display cell, comprising:

a control circuit, after a sustain discharge is performed between said sustain discharge electrodes, applying a second voltage, of a level twice a level of a power supply voltage, which generates a pulse producing a sustain discharge, to at least one of said sustain discharge electrodes, and during or after applying said second voltage, applying a third voltage to an address electrode for selecting said display cell.

18. (PREVIOUSLY PRESENTED) A method of driving a plasma display device in which a first voltage is applied between sustain discharge electrodes so as to perform a discharge in a selected display cell, comprising:

removing wall charges, formed on an address electrode to select said display cell, by a sustain discharge performed between said sustain discharge electrodes.

19. (PREVIOUSLY PRESENTED) The method according to claim 18, wherein said removing comprises applying a second voltage to at least one of said sustain discharge electrodes to form the wall charges and applying a third voltage to said address electrode to produce a self-erase discharge, and

said second voltage forms, on said address electrode by sustain discharge performed between said sustain discharge electrodes, wall charges which undergo self-erase discharge,

between said address electrode and at least one of said sustain discharge electrodes, in said self-erase discharge.

20. (PREVIOUSLY PRESENTED) The method according to claim 19, wherein said removing comprises applying the second voltage to one of said sustain discharge electrodes and setting the other of said sustain electrodes at ground level.

21. (CURRENTLY AMENDED) The method according to claim 2 20, wherein said second voltage is applied to one of said sustain discharge electrodes, and subsequently to the other electrode.

22. (CURRENTLY AMENDED) The method according to claim 4 18, wherein said removing is performed between subfields, each subfield comprising reset, address, and sustain discharge intervals.

23. (PREVIOUSLY PRESENTED) A method of driving a plasma display device wherein a first voltage is applied between sustain discharge electrodes so as to perform a sustain discharge in a display cell, comprising:

after a sustain discharge between said sustain discharge electrodes, applying a second voltage, of a voltage level twice that of a power supply voltage level, to generate a pulse for sustain discharge applied to at least one of said sustain discharge electrodes; and

during or after applying said second voltage, applying a third voltage to an address electrode to select said display cell.

24. (PREVIOUSLY PRESENTED) A method of driving a plasma display device in which a first voltage is applied between sustain discharge electrodes so as to perform a discharge in a display cell, comprising

applying a second voltage of a voltage level twice that of a power supply voltage level, to generate a pulse for sustain discharge, to at least one of said sustain discharge electrodes, as a final pulse producing a sustain discharge between said sustain discharge electrodes; and

during or after applying said second voltage, applying a third voltage to an address electrode to select said display cell.